



Bona Nordic Tone

Craft Oil pre-treatment

Intensely white pre-treatment for Bona Craft oil for that Nordic ambiance.



Bona Nordic Tone is a pre-treatment to Bona Craft Oil or Bona Craft Oil 2K for an intensely white floor. It creates a whitewashed appearance and can be used on both softwood and hardwood. The colour of Bona Nordic Tone can be changed or further intensified by adding up to 5% Bona MixColour to it.

- Rapid drying and easy to apply
- Whiteness can be controlled by number of applications
- Waterborne and completely odourless

TECHNICAL DATA

Product base:	Slightly alkaline solution, pigmentation
Dilution:	Do not dilute
Drying time:	- Between applications: 1-2 hours ¹ - Before oiling: 5-10 hours ¹ ¹ under normal indoor conditions, 20°C/60% R.H. Ensure proper ventilation.
Application tools:	Bona applicator sleeve.
Consumption:	approx. 8-10 m ² /litre (100-120 g/m ²) depending on wood type.
Safety:	Unclassified.
Fire risk:	No.
Cleaning:	Clean tools with water and soap. Dried material can be scrubbed off with water and soap.
Shelf life:	3 years, from the date of production, in unopened original container.
Storage/transport:	The temperature must not fall below +5°C or exceed +30°C during storage and transport.

23/05/17

This data sheet replaces all previous versions
please check bona.com to ensure you have the
latest version.



Bona Nordic Tone

Craft Oil pre-treatment

Intensely white pre-treatment for Bona Craft oil for that Nordic ambiance.

Disposal:	Waste and emptied containers should be handled in accordance with local regulations.
Sizes:	3 x 5 litres.

Additional detailed information is noted in the appropriate Safety Data Sheet.

PREPARATION

Surface must be well sanded, dry and free from sanding dust, oil, wax and other contamination. Empty half of the can into a clean, plastic bucket. Shake the can vigorously and pour the remaining content into the bucket. Stir thoroughly before use and occasionally during use. If using several containers of Bona Nordic Tone, then all material should be mixed into one container to ensure consistent results. Optimal application conditions are between 20-25°C and 30-60% relative humidity.

Minimum temperature for use is 16°C.

Important! Tropical wood or chemically treated wood can trigger unforeseen reactions or bleed wood extracts. Always test on a small area to ensure compatibility and desired results before use.

TREATMENT SCHEDULE

Alternative One

- 1 x Bona Nordic Tone
- 1 x Bona Craft Oil or Bona Craft Oil 2K, Neutral or Coloured
- 1 x Bona Hard Wax Oil

Alternative Two

- 1 x Bona Nordic Tone
- 1 x Bona Craft Oil or Bona Craft Oil 2K

When combining Bona Nordic Tone with coloured oils, we recommend sealing the surface with one layer of Bona Hard Wax Oil as described in alternative one, to simplify maintenance and prevent colour from wearing off.

In high traffic areas consider ending with two layers of Bona Hard Wax oil for increased protection against wear.

APPLICATION

1. Using an application sleeve or a fine, wide floor brush, apply one even layer of Bona Nordic Tone in the direction of the wood at 8-10 m²/litre (120-100 g/m²). Overlap wet-on-wet.
2. If more intensity is desired or if the first application is uneven, then it is possible to apply a second layer after 1 - 2 hours.
3. Allow the final application to dry for 5-10 hours.
4. Gently sand the surface with a Bona Scrad Pad attached under a buffing machine (low rpm). Move the machine quickly and systematically.
5. Vacuum to remove dust.
6. Apply Bona Craft Oil or Bona Craft Oil 2K in the preferred colour.
7. Remove surplus oil with cotton cloths and allow surface to dry overnight, minimum 12 hours.
8. If a coloured oil has been used then we advise to apply an additional layer of Bona Hard Wax Oil to protect the effect colouration.

23/05/17

This data sheet replaces all previous versions
please check bona.com to ensure you have the
latest version.



Bona Nordic Tone

Craft Oil pre-treatment

Intensely white pre-treatment for Bona Craft oil for that Nordic ambiance.

IMPORTANT

Bona Nordic Tone should never be used as the final treatment. Observe that the product cannot prevent the wood changing colour due to tannin bleed, the movement of natural oils or the effects of UV light in the short or long term.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and extensive testing but makes no claim to be complete. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice from Bona before use. Bona can only guarantee its products and not the construction as a whole. Observe recommendations from flooring manufacturer and the provisions of relevant standards.

23/05/17

This data sheet replaces all previous versions
please check bona.com to ensure you have the
latest version.