



Bona Shield R

RESILIENT FLOOR MAINTENANCE

Polyurethane reinforced maintenance coating for resilient flooring.



Bona Shield R is a polyurethane-reinforced maintenance coating for resilient flooring. Developed specifically for surfaces renovated with the Bona Resilient System but also ideal for use on other resilient flooring surfaces such as linoleum and PVC.

- High durability
- Quick drying
- Effective protection

TECHNICAL DATA

Product type:	Matt = Acrylate/Polyurethane, Gloss = Polyurethane
Sheen:	available in Matt & Gloss sheen
Dilution:	Do not dilute
Drying time:	1–2 hours at 20°C/60% R.H.
Application tools:	Bona Polish Applicator
Application rate:	30-50m ² /litre
Safety:	Unclassified
Cleaning:	Clean tools in soap and water. Dried stains can be removed with Bona Deep Clean Solution
Shelf life:	2 years from date of production, in unopened original container
Storage/transport:	The temperature must not fall below +5°C or exceed +30°C during storage and transport
Disposal:	Waste and emptied containers should be handled in accordance with local regulations.
Pack size	3 x 5 litres



Bona Shield R

RESILIENT FLOOR MAINTENANCE

Polyurethane reinforced maintenance coating for resilient flooring.

PREPARATION

It is important that the flooring is cleaned thoroughly prior to the application of Bona Shield R as any residual dirt will be trapped in the coating and may be unsightly.

Clean the flooring with Bona Clean R50, if the flooring is heavily soiled use Bona PowerRemove R.

Test adhesion prior to use, especially if the maintenance history of the flooring is unknown. Wax and certain types of polish will diminish adhesion. In such cases full stripping of the old maintenance coating is necessary.

APPLICATION

1. Ensure the floor is dry and free from any residual cleaner or other contamination.
2. Shake container thoroughly before use.
3. The product can be poured in a bead directly onto the floor, work systematically to distribute a thin even coat across the entire surface.
4. If required, it is possible to apply a second coat of polish after 1-2 hours.

For best results, avoid heavy traffic until the next day.

MAINTENANCE

Clean and maintain floor on a regular basis with Bona Clean R50 or Bona Clean R60, consult respective Technical Data Sheets for detailed instructions. Periodically re-apply Bona Shield R as required, the interval will vary according to local wear conditions.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and extensive testing but makes no claim to be complete. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice from Bona before use. Bona can only guarantee its products and not the construction as a whole. Observe recommendations from flooring manufacturer and the provisions of relevant standards.

2023-05-15

This data sheet replaces all previous versions.
Please check bona.com to ensure that you have the latest version